



ARMORIUS

GLOSS PPF COATING



Facilità d'uso
Easy to use



Protezione dal Traffic Film
Traffic Film Protection



Protezione dai raggi UV
UV Protection



Anti-ingiallimento
Anti-yellowing

DESCRIPTION

Armorius Matt is a ceramic coating specifically developed for the protection of Paint Protection Film (PPF) and matte- or satin-finish wrapping.

Its advanced formulation creates an invisible, hydrophobic protective barrier that isolates the film from environmental contamination, preserving its colour uniformity, texture and original aesthetic appearance, without polishing or altering the finish.

Designed for elastic and heat-sensitive materials such as TPU, Armorius Matt protects the film while keeping its functional properties unaltered, including the self-healing ones.

FEATURES AND BENEFITS

Anti Traffic Film Protection

Reduces the adhesion of oily, mineral and organic road contamination, preventing its infiltration into the microstructure of the film.

Controlled Hydrophobic Barrier

Promotes water sheeting and limits the formation of limescale stains and residue, without altering the matte effect.

UV Protection

Helps counteract fading, yellowing and colour variations caused by prolonged sun exposure.

Full Respect for the Matt Finish

Keeps the original matte or satin appearance intact, without adding gloss, reflections or unwanted shine.

PPF Self-Healing Compatibility

Does not interfere with the self-healing properties of the films.


Chemical Resistance

Protects the surface from urban smog, acid rain, atmospheric agents and detergents.

ACCESSORIES



Coating Cloth



Coating applicator



Protective masks



Protective gloves

SPECIFICATIONS



Up to 5 years
or 50,000 km



Contact angle



Water-repellent barrier



Silkness

ADVANTAGES

- Keeps the matte appearance uniform over time
- Reduces dirt adhesion
- Makes cleaning easier without polishing
- Reduces the need for aggressive decontamination treatments
- Preserves the aesthetics and functionality of the PPF
- Increases the overall lifespan of the film

SURFACE PREPARATION

For optimal results, the surface must be:

- Perfectly clean
- Free of contamination
- Dry
- Properly degreased before application

In the presence of visible contamination, the following is recommended:

- Mineral decontamination with specific acidic detergents
- Removal of organic contamination with alkaline detergents
- Intensive cleaning with dedicated deep-cleaning detergents

FOR PRODUCT SAFETY INFORMATION, REFER TO THE SAFETY DATA SHEET OR THE LABEL.



ARMORIUS

GLOSS PPF COATING



**PFAS FREE
COATINGS**



Facilità d'uso
Easy to use



Protezione dal Traffic Film
Traffic Film Protection



Protezione dai raggi UV
UV Protection



Anti-ingiallimento
Anti-yellowing

DIRECTIONS

1. Wash and thoroughly decontaminate the surface.
2. Degrease the film with a suitable product.
3. Apply Armorius Matt evenly with the coating applicator.
4. Remove any excess with a microfiber cloth.
5. Allow to cure according to the indicated times.

WARNINGS

Apply on a cool surface not exposed to direct sunlight.
Avoid contact with water in the hours following application.
Consult the safety data sheet before use.

SURFACE





PPF films, matte wraps

VEHICLES



AVAILABLE FORMATS

Code	Format		
LAB150	50 ml bottle	1	180
LAB158	20 ml bottle	1	180

FOR PRODUCT SAFETY INFORMATION, REFER TO
THE SAFETY DATA SHEET OR THE LABEL.